

ELG5375: Digital Communications

Lecture 10

Dr. Sergey Loyka

EECS, University of Ottawa

April 10, 2026

Digital Communications: fundamental limits

- from information theory¹
- single user: channel capacity: [bit/s] or [bit/ch. use]
- benchmark for actual system performance
- optimal system design (Tx, Rx)
- much less is known about networks

¹T.M. Cover, J.A. Thomas, Elements of Information Theory, Wiley, 2006.

Fundamental Limit to Reliable Communication

- from information theory²
- **objectives:**
 - maximize data rate
 - keep low (minimize) error rate
 - under constrained Tx power & bandwidth
- Shannon'48: **channel capacity** = the largest possible rate of reliable communication over that channel

²T.M. Cover, J.A. Thomas, Elements of Information Theory, 2006

Fundamental Limit: Channel Capacity

- largest data rate s.t. power & reliability constraints
- AWGN channel:

$$R < C = \Delta f \log(1 + \gamma) \quad [\text{bit/s}] \quad (1)$$

- C = channel capacity [bit/s]
- Δf = channel bandwidth [Hz]
- $\gamma = P_s/P_n$ = analog SNR
- power constraint: Tx power $\leq P_s$
- reliability constraint: arbitrary-low error probability
- no limits on Tx/Rx/complexity
- C : fundamental limit due to nature, not technology


Fundamental Limit: Channel Capacity

- largest data rate s.t. power & reliability constraints


$$R < C = \Delta f \log(1 + \gamma) \text{ [bit/s]} \quad (2)$$

- **the most fundamental result**
- best Tx/Rx strategies
- (almost) error-free transmission:
 - possible if $R < C$
 - not possible otherwise

Claude Shannon, Farther of Information Theory [1948]



- Farther of Information Theory
- Born: 30. Apr. 1916, Michigan, USA
- Died: 24 Feb. 2001, Massachusetts, USA



Channel Capacity: two fundamental resources

From the capacity expression,

$$C = \Delta f \log(1 + \gamma) \text{ [bit/s]} \quad (3)$$

C can be increased by increasing

1. bandwidth Δf (expensive in wireless)
2. power P_s , via the SNR $\gamma = P_s/P_n$
3. anything else?

Fundamental Limit: Channel Capacity

- largest data rate s.t. power & reliability constraints

$$R < C = \Delta f \log(1 + \gamma) \text{ [bit/s]} \quad (4)$$

- Q1: **why** C (or R) is limited?
- Q2: **why** by Δf and γ ?

Channel Capacity & M-ary Modulation




Figure: The constellation capacity of M-PAM³

³Y. Han, Optimization of Modulation Constrained Digital Transmission, MS Thesis, University of Ottawa, 2017.

Fundamental Limit: Channel Capacity

- how to approach C ? \rightarrow best modulation/coding⁴
- $R = C$ is not possible, but R can be close to C
- in practice,

$$R = \log(1 + \gamma/\Gamma) \text{ [bit/s/Hz]} \quad (5)$$

$\Gamma > 1$ is the SNR gap to capacity


- $\Gamma \rightarrow 1$ for good (capacity-approaching) system
- depends on modulation and coding⁵⁶

⁴D.J. Costello and G.D. Forney, Channel coding: The road to channel capacity, *Proc. IEEE*, vol. 95, no. 6, Jun. 2007.

⁵G.D. Forney, G. Ungerboeck, Modulation and Coding for Linear Gaussian Channels, *IEEE Trans. Info. Theory*, v. 44, no. 6, pp. 2384–2415, Oct. 1998.

⁶J. Cioffi, EE 379A - Digital Communication: Signal Processing, Stanford University.

SNR-Gap-to-Capacity in Practice⁷



⁷D.J.C. MacKay, Information Theory, Inference and Learning Algorithms, Cambridge University Press, 2003, p.15, 162.


Spectral/Power Efficiency: Fundamental Tradeoff

- power efficiency: $\gamma_b = \text{SNR}(\text{energy})/\text{bit}$
- spectral efficiency: $R/\Delta f$ [bit/s/Hz]
- the tradeoff:

$$\gamma_b \geq \frac{2^{R/\Delta f} - 1}{R/\Delta f} \geq \ln 2 = -1.6 \text{ dB} \quad (6)$$

- follows from $R < C = \Delta f \log(1 + \gamma)$ with $E_b = P_s T_b$, $\gamma_b = \gamma \Delta f / R$
- LB: $\uparrow R/\Delta f$ (SE)
- min LB = -1.6 dB/bit
- **Q:** prove (6) and properties

Spectral/Power Efficiency: Fundamental Tradeoff






Figure 9.6 Bandwidth-efficiency plane.

From Shannon to Practice

- Shannon (1948): capacity is achievable
- But his proof was **non-constructive** (existence only)
- Question: can we build practical codes that approach capacity?

Answer (after 5 decades): **yes**

Progress Towards the Capacity⁸

Progress toward the Shannon limit

The original turbo codes: about **0.7 dB** from capacity

C. Berrou, A. Glavieux, and P. Thitimajshima, Near Shannon limit error-correcting coding and decoding: Turbo codes, *IEEE Int. Communications Conference*, 1993.

Irregular LDPC codes: about **0.1 dB** from capacity

T.J. Richardson and R. Urbanke, The capacity of low-density parity-check codes, *IEEE Transactions on Information Theory*, February 2001.

How about **0.01 dB** from capacity? And **0.001 dB**?

J. Boutros, G. Caire, E. Viterbo, H. Sawaya, and S. Vialle, Turbo code at **0.03 dB** from capacity limit, *IEEE Symp. Inform. Theory*, July 2002.

S-Y. Chung, G.D. Forney, Jr., T.J. Richardson, and R. Urbanke, On the design of low-density parity-check codes within **0.0045 dB** of the Shannon limit, *IEEE Communications Letters*, February 2001.

Conclusion: *For all practical purposes, Shannon's puzzle has been now solved and Shannon's promise has been achieved!*

⁸A.Vardy, What's New and Exciting in Algebraic and Combinatorial Coding Theory? Plenary Talk at ISIT-06.

Timeline of Modern Codes

- 1950s–1990s: algebraic codes (Reed–Solomon, BCH)
- 1993: **Turbo codes**
- 1990s–2000s: **LDPC codes** (rediscovered)
- 2009: **Polar codes** (Arikan)

All of these can operate very close to capacity.

Key Idea: Iterative Decoding

- Modern codes use **probabilistic decoding**
- Messages are refined iteratively
- Often implemented via message passing

Instead of hard decisions, decoders work with probabilities.

Modern Coding: Landmark Papers

- C. Berrou, A. Glavieux, and P. Thitimajshima, Near Shannon Limit Error-Correcting Coding and Decoding: Turbo Codes, *ICC*, 1993
- R. G. Gallager, *Low-Density Parity-Check Codes*, 1963 (PhD thesis)
- E. Arıkan, Channel Polarization: A Method for Constructing Capacity-Achieving Codes, *IEEE Trans. Info. Theory*, 2009

References on coding/modulation

- E. Biglieri, *Coding for Wireless Channels*, Springer, 2005.
- W.E. Ryan and S. Lin, *Channel Codes: Classical and Modern*, Cambridge, U.K.: Cambridge Univ. Press, 2009
- T.K. Moon, *Error Correction Coding—Mathematical Methods and Algorithms*, New York, NY, USA: Wiley, 2005.
- I.B. Djordjevic, W. Ryan, and B. Vasic, *Coding for Optical Channels*, New York, NY, USA: Springer, 2010.
- I.B. Djordjevic, *Advanced Optical and Wireless Communications Systems*, Springer, 2018.

References on coding/modulation

- D.J. Costello and G.D. Forney, Channel coding: The road to channel capacity, *Proc. IEEE*, vol. 95, no. 6, pp. 1150–1177, Jun. 2007.
- D.J. Costello *et al.*, Applications of error-control coding, *IEEE Trans. Inf. Theory*, vol. 44, no. 6, pp. 2531–2560, Oct. 1998.
- G.D. Forney and G. Ungerboeck, Modulation and coding for linear Gaussian channels, *IEEE Trans. Inf. Theory*, vol. 44, no. 6, pp. 2384–2415, Oct. 1998.
- A. Leven and L. Schmalen, Status and recent advances on forward error correction technologies for lightwave systems, *IEEE J. Lightwave Technol.*, vol. 32, no. 16, pp. 2735–2750, Aug. 2014.
- M. Nakazawa *et al.*, Extremely higher-order modulation formats, *Optical Fiber Telecommunications: Systems and Networks*, 2013, vol. B, pp. 297–336.

References on modern coding

- IEEE ComSoc: Best Readings in Polar Coding, available online.
- Recent Advances in Capacity Approaching Codes, IEEE JSAC, Feb. 2016.
- V. Bioglio et al, Design of Polar Codes in 5G New Radio, IEEE Comm. Surveys & Tutorials, vol. 23, no. 1, 2021.
- M. Sy, Demystifying 5G Polar and LDPC Codes: A Comprehensive Review and Foundations, Feb. 2025.
- https://en.wikipedia.org/wiki/Low-density_parity-check_code
- [https://en.wikipedia.org/wiki/Polar_code_\(coding_theory\)](https://en.wikipedia.org/wiki/Polar_code_(coding_theory))
- https://en.wikipedia.org/wiki/Turbo_code

Record-High 17.3-bit/s/Hz Spectral Efficiency Transmission over 50 km Using Probabilistically Shaped PDM 4096-QAM

**Samuel L.L. Olsson^{1,*}, Junho Cho¹, Sethumadhavan Chandrasekhar¹,
Xi Chen¹, Ellsworth C. Burrows¹, and Peter J. Winzer¹**

¹Nokia Bell Labs, Holmdel, New Jersey, 07733, United States

16384-QAM TRANSMISSION AT 10 GBD OVER 25-KM SSMF USING POLARIZATION-MULTIPLEXED PROBABILISTIC CONSTELLATION SHAPING

Xi Chen, Junho Cho, Andrew Adamiecki, and Peter Winzer

Nokia Bell Labs, Holmdel, New Jersey, United States

10.66 Peta-Bit/s Transmission over a 38-Core-Three-Mode Fiber

Georg Rademacher⁽¹⁾, Benjamin J. Puttnam⁽¹⁾, Ruben S. Luís⁽¹⁾, Jun Sakaguchi⁽¹⁾,
Werner Klaus⁽¹⁾, Tobias A. Eriksson^(1,2), Yoshinari Awaji⁽¹⁾, Tetsuya Hayashi⁽³⁾,
Takuji Nagashima⁽³⁾, Tetsuya Nakanishi⁽³⁾, Toshiki Taru⁽³⁾, Taketoshi Takahata⁽⁴⁾,
Tetsuya Kobayashi⁽⁴⁾, Hideaki Furukawa⁽¹⁾, and Naoya Wada⁽¹⁾

⁽¹⁾*National Institute of Information and Communications Technology, Photonic Network System Laboratory, 4-2-1,
Nukui-Kitamachi, Koganei, Tokyo, 184-8795, Japan*

⁽²⁾*Royal Institute of Technology (KTH), AlbaNova University Center, 106 91 Stockholm, Sweden*

⁽³⁾*Sumitomo Electric Industries, Ltd., 1 Taya-cho, Sakae-ku, Yokohama 244-8588, Japan*

⁽⁴⁾*Optoquest Co. Ltd., 1335 Haraichi, Ageo, Saitama 362-0021, Japan*

georg.rademacher@nict.go.jp

State-of-the-art (in fiber optical comm.)

"World Record Optical Fiber Transmission Capacity Doubles to 22.9 Petabits per Second", NICT, 2023.

49th European Conference on Optical Communications (ECOC 2023)

Glasgow, UK
1–5 October 2023

22.9 Pb/s Data-Rate by Extreme Space-Wavelength Multiplexing

B. J. Puttnam⁽¹⁾, M. van den Hout^(1,2), G. Di Sciullo^(1,3), R. S. Luis⁽¹⁾, G. Rademacher^{(1)*},
J. Sakaguchi⁽¹⁾, C. Antonelli⁽³⁾, C. Okonkwo⁽²⁾, and H. Furukawa⁽¹⁾




⁽¹⁾ NICT, 4-2-1, Nukui Kitamachi, Koganei, 184-8795 Tokyo, Japan, E-mail:ben@nict.go.jp

⁽²⁾ Eindhoven University of Technology, The Netherlands ⁽³⁾ University of L'Aquila and CNIT, 67100, L'Aquila, Italy. * now with INT, University of Stuttgart, Pfaffenwaldring 47, 70569 Stuttgart, Germany.

Abstract *We transmit 750 wavelength channels covering 19 THz bandwidth over a few-mode multi-core fiber with 114 spatial channels, recording a total GMI-estimated data-rate of 24.7 petabit/second and 22.9 Pb/s after LDPC decoding, both exceeding 200 Tb/s per spatial channel.*

State-of-the-art (in fiber optical comm.)

"World Record Optical Fiber Transmission Capacity Doubles to 22.9 Petabits per Second", NICT, 2023.

			This study
Fiber type	38 core, 3 mode	4 core	38 core, 3 mode
	Mar. 2020	May 2022	Oct. 2023
Fiber cross section			
Spatial channels	114	4	114
Data rate (Pb/s)	10.66	1.02	22.9
Transmission distance (km)	13	51.7	13
Bandwidth (THz), Wavelength band	9.2 C, L	20 S, C, L	18.8 S, C, L
QAM order	64 /256	256	256

Summary

- Fundamental limits in digital communications
- Channel capacity
- Spectral/power efficiency tradeoff
- How to approach the capacity ?
- SNR gap to capacity

Reading

- T.M. Cover, J.A. Thomas, Elements of Information Theory, Wiley, 2006.
- S. Haykin, Digital Communication Systems, Wiley, 2014.
- J.M. Wozencraft, I.M. Jacobs, Principles of Communication Engineering, Wiley, 1965.
- Other books/papers (see the reference list).

Note: Do not forget to do end-of-chapter problems. Remember the learning efficiency pyramid!